



PORSCHE

CHECKLIST for the Driver

Porsche Cars North America

Driving	<ul style="list-style-type: none">• Wear appropriate clothes (uniform, clean gloves, special shoes).• Max. speed when driving onto ramps = walking speed.• Do not exceed 10 MPH.• Observe a max. engine speed of 1500 rpm.• Do not drive vehicles with flat tires or other abnormal conditions.• The windshield must be clean and clear when driving.
Transport	<ul style="list-style-type: none">• Do not deliver any Porsche vehicle to any address other than what appears on the Monroney label. Any requests for alternative delivery must be approved by PCNA in advance.• Notify your dispatcher when you encounter any delays, such as foul weather or mechanical failure. It is important that PCNA be notified of all delays so that dealers and customers may be notified.

Loading

- Work gloves, arm and hand jewelry must be removed.
- It is not permitted to carry keys, bottle openers or similar on belts.
- Prepare the truck for loading, set up the ramps for loading Porsches.
- Compare the VIN number on the vehicle to the Monroney Label and your Gate Pass to ensure they match.
- Inspect the unit (especially exposed rims and tires).
- Unzip the driver side roll-up door in the “full body cover”, roll up and attach the roll-up door to the roof of the unit.
- Inspect the driver’s area of the interior and the accessories. Please make sure that the floor mats (when applicable) are in the trunk of the Sports Cars.
- If there are concerns with the vehicle the local Representative of PCNA must be advised immediately.
- Turn on Battery Switch found in front of the driver’s seat (Cayenne) or on top of the hood (Sports Cars).
- Fold both mirrors if they are not needed for loading.
- Release the handbrake.
- Observe safe distances and specific vehicle requirements.
- Switch off all power-consuming devices, completely close windows.
- Turn off the engine, put the car into 1st gear or into position “P” (automatic).
- Apply the handbrake and remove the ignition key.
- Switch off the battery main switch (Cayenne).
- If vehicles are fitted with a full body cover, zip up the door piece.
- Put the vehicle key in a secure place.
- Secure the vehicle, in accordance with the specifications, vehicle type and vehicle position, using wheel straps (one strap per wheel).
- Carefully move the lashing equipment between the vehicles.

Unloading

- Upon arrival at destination, find a suitable, level unloading space.
- In the unloading process, observe all applicable procedures from the loading guidelines.
- Due to Engine Speed Limitation be careful when unloading on public streets.
- Always make sure the person who you are delivering the vehicle to is an authorized dealer representative.
- Have delivery receipt signed (date and time) by dealer personnel.

